

GENERAL NOTES:

A. UNLESS OTHERWISE NOTED:
 1. ALL DIMENSIONS ARE IN INCHES.
 EXCEPT "xxxx" = mm.

B. APPROX WEIGHT: 4500 LBS (2041 KG).


C. SEE ELECTRICAL SCHEMATIC FOR LOAD CAPACITY (KV) RATINGS, VOLTAGE RATINGS, AND BLOWER MOTOR RATING (H.P.)

RECOMMENDED MINIMUM CLEARANCES
 (SEE O & M MANUAL FOR INSTALLATION DETAILS)

NOTE 1) 36" [914] ALL 4 SIDES FOR MAINTENANCE.
 NOTE 2) 36" - 48" [914-1219] ALL 4 SIDES FOR AIR INTAKE.
 NOTE 3) 12-14 FT [3658-4267] FOR TOP HOT AIR EXHAUST.

THIS DRAWING IS PROPERTY OF LOAD BANKS DIRECT AND SHALL REMAIN SO WHILE IN USER'S POSSESSION. THE TECHNOLOGY SHOWN HERE IS STRICTLY PROPRIETARY AND IS NOT TO BE DISCLOSED TO ANY 3RD PARTY WITHOUT LOAD BANKS DIRECT PRIOR CONSENT.

REV 1: Added Side Fork Pockets & Mig Holes (8-28-10)

 Load Banks Direct www.LoadBanksDirect.com		DWG. NO. LT2500-URV2-0L	REV. 1	SHEET 1 of 1
TEXT LOAD BANK, TRAILER READY	DRAWN BY JJF	CHECKD BY MMP	DATE 4/16/18	SIZE A