



GENERAL NOTES:

- A. UNLESS OTHERWISE NOTED:
1. ALL DIMENSIONS ARE IN INCHES.
EXCEPT "xxxx" = mm.
- B. APPROX WEIGHT: 8000 - 12000 LBS (3629-5443 KG)
- C. SEE ELECTRICAL SCHEMATIC FOR LOAD CAPACITY (KVA) RATINGS, VOLTAGE RATINGS, AND BLOWER MOTOR RATING (H.P.)

RECOMMENDED MINIMUM CLEARANCES
(SEE O & M MANUAL FOR INSTALLATION DETAILS)

NOTE 1) 36" [914] ALL 4 SIDES FOR MAINTENANCE.
NOTE 2) 36" - 48" [914-1219] ALL 4 SIDES FOR AIR INTAKE.
NOTE 3) 12-14 FT [3668-4267] FOR TOP HOT AIR EXHAUST.
NOTE 4) LOAD BANK IS SUPPLIED WITH OUTDOOR WEATHERPROOF NEMA-3R-TYPE ENCLOSURE.

<p>Load Banks Direct www.LoadBanksDirect.com</p>		<p>TEXT</p> <p>DWG. NO. RL1250-1875-OL</p> <p>REV. -</p> <p>DATE 10/11/14</p>	
<p>RESISTIVE / REACTIVE LOAD BANK</p> <p>1250 THRU 1875 KVA</p>	<p>1 OF 1</p>	<p>CHECKED BY: MMP</p>	<p>SIZE: A</p>

THIS DRAWING IS PROPERTY OF LOAD BANKS DIRECT AND SHALL REMAIN SO WHILE IN USER'S POSSESSION. THE TECHNOLOGY SHOWN HERE IS STRICTLY PROPRIETARY AND IS NOT TO BE DISCLOSED TO ANY 3RD PARTY WITHOUT LOAD BANKS DIRECT PRIOR CONSENT.